

Features

- ◆ Ultra-wide 4:1 input range
- ◆ Full SMD-Design
- ◆ High efficiency up to 84%
- ◆ Extended operating temperature range -40°C to +85°C
- ◆ Excellent load and line regulation
- ◆ Indefinite short-circuit protection
- ◆ I/O isolation 1'500 VDC
- ◆ Input filter to meet EN 55022, Class A and FCC, level A without external components
- ◆ Shielded metal case with insulated baseplate
- ◆ Lead free design, fully RoHS compliant
- ◆ 3-year product warranty



The TEN 3WI series is a family of dc-dc converter modules with 3W output power, featuring ultra wide 4:1 input voltage ranges of 9-36VDC or 18-75VDC. They come in a DIP-24 plastic package with industry-standard footprint. A high efficiency up to 84% allows operation ambient temperatures of -40°C to +70°C at full load. A built-in EMI input filter complies with EN 55022, class A without need of external components. Further standard features include over voltage protection and continuous short circuit protection. Typical applications for these converters are battery operated equipment and distributed power architectures in communication, instrumentation and industrial electronics, everywhere where isolated, tightly regulated voltages are required

Models

Ordercode	Input voltage range	Output voltage	Output current max.	Efficiency typ.
TEN 3-2410WI	9 – 36 VDC (24 VDC nominal)	3.3 VDC	750 mA	75 %
TEN 3-2411WI		5 VDC	600 mA	79 %
TEN 3-2412WI		12 VDC	250 mA	81 %
TEN 3-2413WI		15 VDC	200 mA	82 %
TEN 3-2422WI		±12 VDC	±125 mA	80 %
TEN 3-2423WI		±15 VDC	±100 mA	80 %
TEN 3-4810WI	18 – 75 VDC (48 VDC nominal)	3.3 VDC	750 mA	76 %
TEN 3-4811WI		5 VDC	600 mA	80 %
TEN 3-4812WI		12 VDC	250 mA	83 %
TEN 3-4813WI		15 VDC	200 mA	84 %
TEN 3-4822WI		±12 VDC	±125 mA	82 %
TEN 3-4823WI		±15 VDC	±100 mA	82 %

Input Specifications

Input current no load /full load	24 Vin models 48 Vin models	20 mA typ. / 150 mA typ. 10 mA typ. / 75 mA typ.
Start-up voltage / under voltage shut down	24 Vin models 48 Vin models	9 VDC / 8.5 VDC typ. 18 VDC / 16 VDC typ.
Surge voltage (1 sec. max.)	24 Vin models 48 Vin models	50 V max. 100 V max.
Reverse voltage protection		0.5 A max.
Conducted noise (input)		EN 55022 level A, FCC part 15, level A

Output Specifications

Voltage set accuracy		±2.0 % max.
Regulation	– Input variation Vin min. to Vin max. – Load variation 10 – 100 %	1.0 % max.
	single output models dual output models	1.0 % max. 3.0 % max. (balanced load)
Ripple and noise (20 MHz Bandwidth)		75 mVpk-pk max
Temperature coefficient		0.02 %/K
Current limitation		>110 % of Iout max., constant current
Transient response (25% load step change)		300 µs typ.
Short circuit protection		indefinite (automatic recovery)
Capacitive load	3.3 VDC models 5 VDC models 12 VDC models 12 VDC models ±12 VDC models ±15 VDC models	680 µF max. 470 µF max. 330 µF max. 220 µF max. 150 µF max. (for each output) 100 µF max. (for each output)

General Specifications

Temperature ranges	– Operating – Case temperature – Storage	–40°C to +85°C +100°C max. –55°C to +125°C
Derating		3.5 %/K above 70°C
Humidity (non condensing)		95 % rel H max.
Reliability, calculated MTBF (MIL-HDBK-217F, at +25°C, ground benign)		>1 Mio. h
Isolation voltage (60 sec.)	– Input/Output	1'500 VDC
Isolation capacitance	– Input/Output	380 pF typ
Isolation resistance	– Input/Output (500 VDC)	>1'000 M Ohm
Switching frequency		350 kHz typ. (Pulse width modulation PWM)
Safety standards		UL 60950-1 , IEC/EN 60950-1
Safety approvals	– CSA certificate according UL 60950-1 – CB test report	www.tracopower.com/products/ten3wi-csa.pdf www.tracopower.com/products/ten3wi-cb.pdf
Environmental compliance	– Reach – RoHS	www.tracopower.com/products/ten3wi-reach.pdf RoHS directive 2011/65/EU

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Casing material	non conductive black plastic
Potting material	epoxy (UL94V-0 rated)
Weight	12 g (0.42 oz)
Soldering temperature	max. 265°C / 10 sec.

Technical drawing of a rectangular plate with dimensions and hole locations. The drawing includes a top view and a side view.

Top View Dimensions:

- Overall width: 32 ± 0.5 (1.25 ± 0.02)
- Overall height: 20.0 (0.787)
- Distance from left edge to center of first hole: 4.5 ± 0.5 (0.18 ± 0.02)
- Distance between centers of first two holes: 2.54 (0.1)
- Distance between centers of last two holes: 5.08 (0.2)
- Distance from center of first hole to center of last hole: 22.86 (0.9)
- Distance from center of last hole to right edge: 5.08 (0.2)
- Distance from top edge to center of first hole: 15.24 (0.6)
- Distance from top edge to center of last hole: 15.24 (0.6)
- Distance from bottom edge to center of first hole: 2.4 (0.094)
- Distance from bottom edge to center of last hole: 2.4 (0.094)

Side View Dimensions:

- Overall height: 10.2 ± 0.5 (0.4 ± 0.02)
- Distance from bottom edge to center of first hole: 50 (0.2)
- Distance from center of first hole to center of last hole: 50 (0.2)
- Distance from center of last hole to top edge: 50 (0.2)

Pin-Out		
Pin	Single	Dual
2	-Vin (GND)	-Vin (GND)
3	-Vin (GND)	-Vin (GND)
9	No pin	Common
11	No function	-Vout
14	+Vout	+Vout
16	-Vout	Common
22	+Vin (Vcc)	+Vin (Vcc)
23	+Vin (Vcc)	+Vin (Vcc)

Tolerances ± 0.5 (± 0.02)

TRACO
ELECTRONIC AG

Rev. 02/13